## **Datasheet**

## NHS 300ev **Standard Line**

NHS 300ev is a side-fed chipper (90° in relation to travel-direction), which is a great advantage for clearing along paths and roads.

With vertical feed rollers and hinged feed box, the daily servicing of blades and Counter blades is exceptionally easy!

It is equipped with tow bar (wagon-coupling) for light tipper or equivalent. (max. Ball pressure: 500kg / max. Pull: 2000 kg.)

NHS 300ev is for external hydraulics (oil supply from tractor)



Max. Log diameter [mm]	300
Min./max. Power input [HP]	68/130
Revolutions PTO [rpm]	1000
Revolutions, Chipping Disc [rpm]	1000
Blades (hardened) [pcs.]	4
Counter blades [pcs.]	1
Cut per revolution [pcs.]	4
Chipping Disc diameter [mm] / Weight [kg]	Ø960/225
Hydraulic feedroller/feedrollers	$\checkmark$
Liters per minute [min./max.]	45/80
Blade-adjustment (chip-size) [mm]	10-15
NHS InfoCon	$\checkmark$
Hourcounter/ serviceplanner	$\checkmark$
Chip-production per hour [m³]	30
Opening, funnel - W/H [mm]	1170/ 800
Opening, feedrollers - H/W [mm]	300/ 300
Discharge Pipe	$\checkmark$
Overrunning clutch	$\checkmark$
Safety clutch, PTO-shaft	$\checkmark$
3 pt. suspension category	2
Length [mm]	2300
Width [mm]	1900
Height [mm]	3000
Weight [kg.]	1450
Shipping dim. in meters [L/W/H]	2,3/1,9/2,4
Noise (workplace measurement) [dBA]	105
—NHS=Maskinfabrik A/S   Bergsøesvej 6   DK-8600 Silkeborg   Tel: +45 8720 6500   E-mail: nhs@nhs.dk   www.nhs-woodchippers.com	